

2 in 1 Hout

WOOD PRIMER AND VARNISH

A pioneering, dual-action, transparent protective and decorative wood stain suitable for both outdoor and indoor use. This easy-to-apply stain provides maximum, long-lasting protection along with excellent gloss and durability, enhancing the appearance of your wood surfaces.



TECHNICAL CHARACTERISTICS

Base	Alkyd
Appearance	Thin Liquid
Shade	Transparent
Viscosity	100 – 300 mPa•s at 23°C
Density	0.95 ± 0,02 gr/cm ³
Gloss 60°	91
Solids etc.	55%
Ideal temperature for applying & drying	15-25°C
Surface Drying	3-4 hrs
Deep Drying	24 hrs
Recoating Time	24 hrs
Yield	12-14 m ² /lt per coating
Dilution	5% with Brush Slovent

NOTE (*): (*) The exact time depends on the temperature and relative humidity prevailing during application and drying.

USES

Ideal for surfaces from:

- Wood

CHARACTERISTICS

- High Gloss
- Long-term durability
- Excellent finish
- High Yield
- Easy to spread
- Resistance to solar radiation
- Resistance to the growth of micro-organisms

SURFACE PREPARATION

-Applies to dry, clean surfaces free of materials that are not contaminated with materials which prevent adhesion.

-The success of the application depends on the correct preparation of the preparation of the substrate and the correct application of the material.

APPLICATION

-Apply the 2 IN 1 HOUT in one or two layers.

-To adjust the fluidity it can be diluted by adding Solvent 5% brush thinner.

-The second coat should be applied after the first coat has dried.

TOOLS CLEANING

While working, keep the tools "wet" in the container or in the paint bucket.

Drain off the paint well from tools into the container and clean them with Nitro Solvent.

STORAGE

One year in closed container, at temperatures between 5° C - 40° C.

RESTRICTIONS

- Do not apply at temperatures below 5°C or above 35°C.
- Do not apply when the air relative humidity is higher than 80%.
- Wet surfaces should be allowed to dry thoroughly before application.
- The freshly painted surface should be protected from the cold and moisture for at least 24hr

VOC CATEGORY

-Product category A/e (D) Interior/exterior varnishes and wood staining products for finishing including opaque wood stain products' of European Directive 2004/42/EC. VOC class limit value: 400 g/l.

Maximum VOC content of VOC content of the ready-to-use product is 399 gr/ltr.