


Chassikote 2 in 1

2 IN 1 METAL PRIMER + ENAMEL

A 2 in 1 Metal Primer + Enamel specifically designed for metal surfaces and car chassis. This versatile product is ideal for both individuals and professionals, providing either a temporary coat until the final coat is applied or a satin paint finish by applying more coats (2-3 in total).



SPECIFICATIONS

Appearance	Viscous liquid
Shades	Different shades
Viscosity	2000 – 2500 mPa•s at 23°C
Density	1,15-1,25 0,02 gr/cm ³ depending on the shade
Surface Drying	2hr
Recoating	24hr
Performance	12-14m ² /lt per coat
Dilution	5% with White Spirit

NOTE (*): The exact time depends on the temperature and relative humidity prevailing during application and drying.

USES

Ideal for surfaces from:

- Metal

CHARACTERISTICS

- Perfect coverage
- Metal Primer + Enamel
- Car Chassis Protection
- Long-Lasting

TOOLS CLEANING

While working, keep the tools "wet" in the container or in the paint bucket. Drain the paint well from the tools back to the box and clean them with White spirit.

STORAGE

One year in closed container, at temperatures between 5° C - 35° C.

SURFACE PREPARATION

- It is applied to dry, clean surfaces free from materials that prevent adhesion.
- The success of the application depends on the correct preparation of the substrate and the correct application of the material.
- Removal of silicone or oils from the surface of the metal with thinner.

APPLICATION

- The surface should be applied in two coats with Chassikote 2 in 1.
- For liquidity adjustment it can be diluted with the addition of 5% - 10% White spirit or with 5% SL-501
- With Chassikote, you can achieve appropriate protection for up to 2-5 years, ensuring your metal surfaces remain in excellent condition. This product offers perfect coverage, anti-corrosion protection, high performance, and very good chemical and mechanical resistance.

RESTRICTIONS

- Do not apply at temperatures below 5°C or above 35°C.
- Do not apply when the air relative humidity is higher than 80%.
- Wet surfaces should be allowed to dry thoroughly before application.

VOC CATEGORY

Product Category A/i (SB) 'One-pack performance coatings' of the EU legislation 2004/42/EU. Maximum limit VOC value of category: 500gr/lit. Maximum VOC concentration of ready to use product 499 gr/lit.