


Lanstrada AC670

ACRYLIC ROAD MARKING PAINT

A high-quality acrylic road marking paint designed to provide exceptional performance and durability for various applications. This special acrylic solvent paint is based on synthetic resins, making it suitable for road marking on asphalt pavements, parking areas, concrete floors, airports, industrial spaces, and sports grounds.



SPECIFICATIONS

Appearance	Thin liquid
Color	White
Viscosity	70-80 KU at 23°C
Density	1.52 ± 0,02 gr/cm ³
Surface drying	10-20 min
Attribution	400-500 g/m ²
Dilution	Up to 5% with Nitro Solvent

NOTE (*): The exact time depends on the temperature and relative humidity prevailing during application and drying.

USES

Ideal for surfaces from:

- Asphalt
- Concrete

CHARACTERISTICS

- Road Marking Solution
- Excellent Adhesion
- High Traffic Resistance

CLEANING OF TOOLS

During the work, keep the tools "wet" in the container or in the paint vessels. Thoroughly drain the paint from the tools back into the box and clean them first with Nitro Solvent and then with soap and water.

STORAGE

Store between 5° to 40° C. If you do not use the whole quantity, close carefully the lid for next use.

PREPARATION OF SUBSTRATE

- It has to be applied in dry and clean surfaces, without materials which prevent the traction of the product.
- The success of application depends on the correct preparation of the substrate and the proper use of the material.
- The surface is cleaned of foreign particles, dust and debris.
- Lankstrada is applied directly to the asphalt surface.

APPLICATION

- The Lankstrada is applied in two layers.
- To adjust the fluidity it can be diluted by adding up to 5% NITRO SOLVENT
- The second coat should be made after the first one has dried.

Boasts excellent adhesion to asphalt, concrete, and other surfaces, ensuring a long-lasting and reliable marking solution. Its high resistance to car tires and adverse conditions, such as frost and high temperatures, guarantees that your markings remain intact and visible even in the most demanding environments.

LIMITATIONS

- Do not apply at temperatures below 5°C or above 35°C
- Do not apply when the relative humidity of more than 80%
- Wet surfaces should be allowed to dry thoroughly before application

VOC CATEGORY

Category: A/i (SB) 'One-pack performance coatings' of 2004/42/EC. Maximum limit VOC value of category: 500gr/ltr. Maximum VOC concentration of ready to use product: 495gr/ltr.