


Rapid Protector

FAST DRYING METAL PRIMER

A fast-drying metal primer designed to ensure perfect adhesion between metal surfaces and alkyd paints. This alkyd-based primer provides a matte finish that enhances the bond between the metal and the final paint layer, ensuring a long-lasting and durable result.



SPECIFICATIONS

Appearance	Viscous liquid
Hue	White, Black, Grey, Red, Brown
Viscosity	2000–2500 mPa•s at 23°C
Density	1.50 ± 0,02 gr/cm ³
Surface drying	10 min
Recoating time (*)	1-2 hr
Yield	10-12 m ² /lt per layer
Dilution	5% with Spray Gun Solvent

NOTE (*): The exact time depends on the temperature and relative humidity prevailing during application and drying.

USES

Ideal for surfaces from:

- Metal

CHARACTERISTICS

- Fast drying
- Matte Finish
- High Adhesion

RESTRICTIONS

- Do not apply at temperatures below 5°C or above 35°C
- Do not apply when the air relative humidity is higher than 80%
- Wet surfaces should be allowed to dry thoroughly before application.

SURFACE PREPARATION

- It is applied on dry, clean surfaces free of materials that prevent adhesion.
- Application's success depends on the proper preparation of the surface and the correct application of the material.
- Remove silicone or oils from the metal surface with solvent.

APPLICATION

- Apply Rapid Protector on the surface in one or two layers.
- To adjust the fluidity, it can be diluted by adding 5% Spray Gun Solvent.
- The second layer must be applied after the first one has dried.

Diluted with solvent White spirit, Rapid Protector offers high corrosion protection and excellent resistance, making it an ideal choice for various metal surfaces. Experience the fast drying time and exceptional performance of this metal primer.

CLEANING OF TOOLS

While working, keep the tools "wet" in the container or in the paint bucket. Drain off the paint well from tools into the container and clean them with Spray Gun Solvent.

STORAGE

One year in closed container, at temperatures between 5°C – 35°C.

VOC CATEGORY

Product of Category A / i (SB) " One-pack performance coatings" of European Directive 2004/42 / EC.
Category VOC limit value: 500gr/ltr. The maximum VOC content of the ready-to-use product is 499gr/ltr.