

Rust Converter

CONVERTS RUST INTO PROTECTION

An innovative water-soluble product that converts rust into a protective barrier, ensuring your metal surfaces remain safe from corrosion. This rust-stabilizing solution increases the mechanical strength of the surface and extends the shielding time, saving you both time and money by eliminating the need for sanding.



SPECIFICATIONS

Viscosity	30 – 50 sec στους 23°C
Density	1.35 ± 0,02 gr/cm ³
pH	1-2
Surface Drying	2-3 hr
Recoating Time (*)	24 hr
Yield	14-18 m ² /lt

(*) The exact time depends on the temperature and relative humidity during application and drying.

USES

Ideal for surfaces from:

- Metal

CHARACTERISTICS

- Stabilizes the rust
- No need for sanding
- Anticorrosive Protection

TOOLS CLEANING

Drain the paint thoroughly from the tools back into the can and clean them with water.

RESTRICTIONS

- Do not apply at temperatures below 5°C or above 35°C
- Do not apply when relative humidity exceeds 80%
- Wet surfaces should be allowed to dry thoroughly before application.

SURFACE PREPARATION

- It is applied on dry, clean surfaces free of materials that prevent adhesion.
- Stir well before use.

APPLICATION

- RUST CONVERTER is applied in one coat without dilution.
- Any excess material is removed with a dry cloth.
- After 24 hours an anti-corrosive primer and paint is applied to fully protect the metal surface.
- Easy to use and effectively stabilizes rust, providing long lasting protection for your metal surfaces.
- Keep your valuable assets corrosion-free and in optimal condition with this revolutionary solution.

STORAGE

In a closed container and storage temperatures between 5°C and 40°C