

SB WHITE PRIMER FOR WOOD

An solvent based White Primer specifically designed for wood surfaces, chipboard, and metal. This special substrate is ideal for enamel paints and provides perfect coverage, high whiteness, and exceptional adhesion. With Seko, you can trust your surfaces will be well-prepared and protected.



SPECIFICATIONS

Base	Alkyd
Appearance	Thick liquid
Color	White
Viscosity	2000 – 2500 mPa · s at 23° C
Density	1.48 ± 0.02 gr / cm ³
Solids w/w	75%
Ideal application and drying temperature	15 – 25°C
Surface drying	3hr
Deep drying	18hr
Recoat time (*)	24hr
Attribution	16-18m ² / lt per coat
Dilution	5% with White spirit

NOTE (*): The exact time depends on the temperature and relative humidity prevailing during application and drying.

USES

Ideal for surfaces from:

- Wood

CHARACTERISTICS

- Wood Primer
- High Whiteness
- Easy Application

CLEANING OF TOOLS

Keep the tools "wet" in the drum with the paint while working. Drain well the paint from the tools back to the drum and clean them with White Spirit.

STORAGE

Store between 5° to 40°C. If you do not use the whole quantity, close carefully the lid for next use.

PREPARATION OF SUBSTRATE

- It has to be applied in dry and clean surfaces, without materials which prevent the traction of the product.
- The success of application depends on the correct preparation of the substrate and the proper use of the material.

APPLICATION

- Apply two layers of SEKO.
- For regulation of fluidity, it can be diluted with White Spirit 5%.
- The second layer must be applied, after the first one has dried.

easy to work with and stretches out extraordinarily, ensuring a smooth and even application. Its high performance, coupled with very good chemical and mechanical resistance, makes it a reliable choice for your painting projects.

LIMITATIONS

- Do not apply at temperatures below 5°C or above 35°C
- Do not apply when the relative humidity of more than 80%
- The substrate moisture must not be more than 4%
- Wet surfaces should be allowed to dry thoroughly before application
- The fresh-colored surface should be protected from cold and moisture for at least 24 hours

PRECAUTIONS

Flammable liquid and vapour. Causes damage to organs through prolonged or repeated exposure. May cause drowsiness or dizziness. Toxic to aquatic life with long lasting effects. PRECAUTIONARY STATEMENTS: Keep away from heat/ sparks/open flames/hot surfaces. — No smoking. Keep container tightly closed. Wash hands thoroughly after handling. Avoid release to the environment.

Wear protective gloves/protective clothing/eye protection/face protection. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

Call a POISON CENTER or doctor/physician if you feel unwell.

V.O.C. VOLATILE ORGANIC COMPOUNDS

Product Category A/g (SB) 'Primers' of the European Directive 2004/42 / EC. VOC limit value: 350gr / lt. Maximum The VOC content of the ready-to-use product is 349gr /lt.