


WOOD SB PROTECTIVE STAIN

A transparent, semi-glossy wood shield designed for both indoor and outdoor use. This protective stain offers exceptional protection against insects, fungi, and cyanosis (blue spots) while safeguarding the wood from moisture and the harmful effects of solar radiation with its special UV filters.



TECHNICAL CHARACTERISTICS

Shade	Transparent and 9 wood shades
Viscosity	200 – 500 mPa•s at 23°C
Density	0.81 ± 0,02 gr/cm ³
Surface drying	1-2 hrs
Recoating time	24 hrs
Yield	10-12 m ² /lt per coating
Dilution	5% with White Spirit

NOTE (*): (*) The exact time depends on the temperature and relative humidity prevailing during application and drying.

USES

Ideal for surfaces from:

- Wood

CHARACTERISTICS

- Easy to spread
- Resistance to the growth of micro-organisms
- Follows the expansion and contraction of the wood

SURFACE PREPARATION

- It is applied to dry, clean surfaces free from materials that prevent adhesion.
- The success of the application depends on the correct preparation of the substrate and the correct application of the material

APPLICATION

- Apply SEKOXYL in one or two coats
- To adjust the fluidity it can be diluted with the addition of a 5% White Spirit

TOOLS CLEANING

While working, keep the tools "wet" in the container or in the paint bucket.
Drain the paint well from the tools back to the box and clean them with brush thinner.

STORAGE

One year in closed container, at temperatures between 5° C - 35° C.

RESTRICTIONS

- Do not apply at temperatures below 5°C or above 35°C.
- Do not apply when the air relative humidity is higher than 80%.
- Wet surfaces should be allowed to dry thoroughly before application.

VOC CATEGORY

Product Category A/f (SB) 'Interior and exterior minimal build woodstains' of the EU legislation 2004/42/EU. Maximum limit VOC value of category: 700gr/ltr. Maximum VOC concentration of ready to use product 699gr/ltr