


STAMPED FLOOR, CONCRETE AND STONE VARNISH

A decorative embossed coating designed for both interior and exterior surfaces, including stamped floors, concrete, and stone. Achieve a special finish by utilizing special roller blinds during application. Stein provides insulation against moisture ensuring your surfaces remain protected and well-preserved.



SPECIFICATIONS

Base	Alkyd
Appearance	Thin Liquid
Shade	Transparent
Viscosity	150 - 500 mPa·s at 23°C
Density	0.95 ± 0,02 gr/cm ³
Solids etc.	25%
Ideal temperature of application and drying	15 – 25°C
Surface drying	20min
Deep drying	24hr
Recoating Time (*)	24hr
Yield	10-12m ² /lt
Dilution	5% White spirit or Xylene Thinner

NOTE (*): The exact time depends on the temperature and relative humidity prevailing during application and drying.

USES

Ideal for surfaces from:

- Concrete
- Stone
- Industrial flooring
- Forged cement
- Stamped concrete
- Epoxy flooring
- Mosaic flooring

CHARACTERISTICS

- Moisture Insulation
- Special Finish
- Weather Resistant

TOOLS CLEANING

During work keep the tools "wet" inside the container or in the tub with paint. Drain the paint well from the tools back in the container and clean them with nitro solvent.

STORAGE

In closed container, at temperatures between 5°C - 35°C.

SURFACE PREPARATION

- It is applied on dry, clean surfaces free of materials that prevent adhesion.
- The success of the application depends on the proper preparation of the substrate and the correct application of the material

APPLICATION

- Apply the material to the surface with a roller or brush in one or two coats
- For liquidity adjustment it can be diluted with the addition of White spirit or spray gun thinner 5%;
- The second coat should be done after the first one dries.

This durable varnish is highly resistant to adverse weather conditions, making it suitable for both outdoor and indoor use. Stein offers high traction, perfect protection of the floor, and excellent mechanical and chemical resistance.

RESTRICTIONS

- Do not apply at temperatures below 5°C or above 35°C.
- Do not apply when the air relative humidity is higher than 80%.
- Wet surfaces should be allowed to dry thoroughly before application.
- The fresh painted surface should be protected from cold and humidity for at least 24 hours.

VOC CATEGORY

Product Category A/h (SB) 'Binding Primers' of the EU legislation 2004/42/EU. Maximum limit VOC value of category: 750gr/lit. Maximum VOC concentration of ready to use product 749gr/lit.