

ZinkCoat

COLD GALVANIZATION FOR RUST PROTECTION

A powerful antioxidant primer featuring 98% galvanized zinc, designed to provide exceptional protection against strong corrosive agents. This cold galvanizing solution is perfect for ironworks and other applications where superior rust protection is essential.



TECHNICAL CHARACTERISTICS

Hue	Grey
Viscosity	5000 - 7000 mPa·s at 23°C
Density	2.00 ± 0.05 gr / cm ³
Surface drying	30-60min
Recoat time (*)	8-10hr
Yield	14-16m ² / lt per coat
Dilution	5% with pistol solvent

NOTE (*): (*) The exact time depends on the temperature and relative humidity prevailing during application and drying.

USES

Ideal for surfaces from:

- Metal

CHARACTERISTICS

- Strong Adhesion
- Quick Drying
- No drips

LIMITATIONS

- Do not apply at temperatures below 5°C or above 35°C.
- Do not apply when the air relative humidity is higher than 80%.
- Wet surfaces should be allowed to dry thoroughly before application.

PREPARATION OF SUBSTRATE

- It is applied on dry, clean surfaces free of materials that prevent adhesion.
- The success of the application depends on the proper preparation of the substrate and the correct application of the material.
- Remove silicone or oil from the surface of the metal with a solvent.

CLEANING OF TOOLS

While working, keep the tools "wet" in the container or in the paint bucket. Drain off the paint well from tools into the container and clean them with White Spirit.

APPLICATION

- It is applied in one or two layers.
 - For liquidity adjustment it can be diluted by addition of 5% Pistol solvent.
- offers very good adhesion to metallic surfaces, ensuring a long-lasting bond that effectively safeguards your materials from rust and corrosion. Its quick-drying formula saves time and effort, while the non-drip property guarantees a clean and mess-free application.
- Offers very good adhesion to metallic surfaces, ensuring a long-lasting bond that effectively safeguards your materials from rust and corrosion. Its quick-drying formula saves time and effort, while the non-drip property guarantees a clean and mess-free application.

STORAGE

One year in closed container, at temperatures between 5°C – 35°C.

VOC CATEGORY

Product Category A/i (SB) 'One-pack performance coatings' of the EU legislation 2004/42/EU. Maximum limit VOC value of category: 500gr/lit. Maximum VOC concentration of ready to use product 499 gr/lit.